



Fibro-Kustik *Paris*

WW acoustic board according to DIN EN 13168
 WW WI dm / DI dm
 Flame retardant (A2-s1, d0),
 mineral bound
 Fine wool (2mm thread width)



Promoting Sustainable
Forest Management
www.pefc.co.uk

WW EN 13168-T2-L3-W2-P2-CI1-CS(10y)200

Properties:

- Wood-wool board, bound with cement
- Ecologically sound
- good sound absorption
- High vapor permeability
- Diffusion resistance factor 2/5
- General construction supervisory approval Z-23.15-1622

Color design

- Nature
- for an extra charge:
- White sprayed as non-smear in RAL 9010
 - Other colours available when the RAL or NCS-no is provided

Area of Application:

Acoustic ceilings in residential and non-residential construction, e.g. commercial, industrial and public buildings, offices, schools, sports halls, and garages.

Article master	Board thickness in mm	Heat transfer resistance RD m ² K/W	Standard in mm		Weight in kg		Contents per pallet (1200 x 1200mm) (1000 x 1200mm)	
			Length	Width	per m ²	per pallet	Piece	m ²
2590172015	15	0,20	1200/600	600	10,0	962	128	92,16
2590172025	25	0,33	1200/600	600	13,3	710	70	50,40
2590172025	25	0,33	1000/600	600	13,3	710	70	42,00



www.blauer-engel.de/uz132

On request with the world-wide unique indoor air purifying effect:




Edge designs:


Direct mounting, inlay mounting, hidden mounting




GKANTE
Straight edge



FASE05
small beveled edge
5mm



FUGE05
straight edge with all-round
rabbet for 5 mm wide joints
(as of 25 mm)




GK-EIN
Inlay assembly
with straight edges



SF-EIN
Inlay mounting
with rabbet on visible side




SF-EINF05
Inlay mounting
with rabbet on visible side
And all-round rabbet
(as of 25 mm)



VF05
Hidden edge
cannot be removed
(as of 25mm)



VF05-DEM
Grooved along the length
all-round beveled edge
can be removed
(as of 25 mm)



Expert report

Ball-proof wall cladding in accordance with DIN 18032/ Part 3

Product	Thickness in mm	Attachment			Test certificate
		Substructure	Axis distance	Screws	
Fibro-Kustik Paris	25	Wooden battens 80 x 30 mm	≤600mm	Acoustic screws in 45 mm lengths 6 pieces per pallet with 1200x600 mm format	903 1238 000/1/Man/H MPA Stuttgart
Fibro-Kustik Paris	25	CD profile 60 x 27 mm	≤600mm		903 1238 000/1/Man/H MPA Stuttgart

Ball-proof ceiling cladding in accordance with DIN 18032/ Part 3

Product	Thickness in mm	Attachment			Test certificate
		Substructure	Axis distance	Screws	
Fibro-Kustik Paris	25	Wooden battens 80 x 30 mm	≤600mm	Acoustic screws in 45 mm lengths 6 pieces per pallet with 1200x600 mm format	903 1238 000/2/Man/H MPA Stuttgart
Fibro-Kustik Paris	25	CD profile 60 x 27 mm	≤600mm		903 1238 000/2/Man/H MPA Stuttgart

This technical information reflects the current level of our knowledge and experience. Subject to changes without prior notification. Please use the latest version of the product data sheet as levels of experience and knowledge are constantly developing. Please contact our office in the event of doubt. Examples of use described may not account for the specific circumstances of each individual case and we therefore accept no liability for them. Otherwise, only our General Terms of Sale, Delivery and Payment (latest version), of which you are aware, apply.

October 2019